

Sub
C4

1. (currently amended) ~~A method of displaying information by~~
a network kiosk comprising the steps of:

sensing a person within a predetermined distance of the
kiosk;

displaying first information in response to said sensing
step;

timing a time period of displaying the first information;
and

displaying second information which is less distinctive than
the first information if the person does not begin use of the
kiosk within the time period.

B1
cont

2. (currently amended) A method of displaying information by
a network kiosk comprising the steps of:

sensing a person within a predetermined distance of the
kiosk;

displaying first information in response to said sensing
step;

timing a time period of displaying the first information;
and

displaying second information which is less distinctive than
the first information if the person is no longer within the
predetermined distance of the kiosk and the time period has
expired.

3. (currently amended) A method of displaying information by a network kiosk comprising the steps of:

displaying first information;

sensing a person within a predetermined distance of the kiosk;

displaying second information which is more distinctive than the first information in response to said sensing step;

timing a time period of displaying the second information; and

displaying third information if the person is no longer within the predetermined distance of the kiosk and the time period has expired.

4. (currently amended) A method of displaying information by a network kiosk comprising the steps of:

displaying first information;

sensing a person within a predetermined distance of the kiosk;

determining second information for display which is more distinctive than the first information in response to said sensing step;

displaying the second information;

timing a time period of displaying the second information to wait for the person to operate the kiosk;

determining third information for display which is less distinctive than the second information when the person is no longer within the predetermined distance of the kiosk and the time period has expired; and
displaying the third information.

B1
cont

5. (currently amended) A network kiosk comprising:
a display for displaying information;
a proximity sensor; and
a computer which senses a person within a predetermined distance of the kiosk, displays first information in response to sensing the person, times a time period of displaying the first information, and displays second information which is less distinctive than the first information if the person does not begin use of the kiosk within the time period.

6. (currently amended) A network kiosk comprising:
a display for displaying information;
a proximity sensor; and
a computer which senses a person within a predetermined distance of the kiosk, displays first information in response to sensing the person, times a time period of displaying the first information, and displays second information which is less distinctive than the first information if the person is no longer

within the predetermined distance of the kiosk and the time period has expired.

7. (original) The network kiosk as recited in claim 6, wherein the proximity sensor comprises an ambient light sensor which senses a drop in ambient light when the person is within the predetermined distance.

8. (new) A method of attracting a person to a network kiosk comprising the steps of:

B/C added
sensing a person within a predetermined distance of the kiosk;

displaying first information and playing a sound in response to said sensing step;

timing a time period of displaying the first information and playing the sound; and

displaying second information which is less distinctive than the first information and stopping the sound if the person does not begin use of the kiosk within the time period.